

ZUIDBERG

NORTH AMERICA INC

Zuidberg C-Frame Track Specs

- 36" wide x 95" long
- Weight – ~4,600 lb per track
- Warranty – 18 months, unlimited hours
- Lose 40% of ground speed compared to wheels

Compatible Combine Models

- **Case IH**
 - 120 Series: 7120 – 8120 – 9120
 - 130/230 Series: 6130 – 7130 – 7230 – 8230 – 9230
 - 140/240 Series: 6140 – 7140 – 7240 – 8240 – 9240
 - 150/250 Series: 6150 – 7150 – 7250 – 8250 – 9250
- **Gleaner** R65 - S67 – S77 – S68 – S78 – S88
- **John Deere**
 - S600 Series: S660 – S670 – S680 – S690
 - S700 Series: S760 – S770 – S780 – S790
 - For X9 1000 and X9 1100 – Send fitment guide (we don't know for sure if they fit)
- **Massey Ferguson** 9545 – 9565 – 9520 – 9540 – 9560
- **New Holland** CX5080 – CX5090 – CX6080 – CX6090 – CX7080 – CX7090 – CX8070 – CX8080 – CX8090
- **New Holland** CR7.90 – CR8.80 – CR8.90 – CR9.80 – CR9.90 – CR10.90

Features and Benefits:

Maintenance

Feature: Oil-filled hubs with sight glass

Benefits: Bearings are lubricated without pushing grease, easy to visually inspect

Feature: Central, enclosed service port

Benefits: Grease zerks are out of the mud, and easy to access. Push grease in 1x per day.

ZUIDBERG

NORTH AMERICA INC

Mounting

Feature: Built in fork slots

Benefits: Our track bolts directly to the hub (10 bolt pattern). Simply lift the track up to the hub using the fork slots.

Feature: Hydraulic Tension

Benefits: Simple to tension, only need to do once per year

- Connect the provided hose to the coupler in the service port of the track.
- Connect the provided gauge in the service port of the track

- Connect the other end of the provided hose to an SCV on tractor, skid loader, fork truck, etc.
- Open up valve in the service port of the track
- Turn on hydraulic flow, aim for 110 bar (1600 psi)
- If you overshoot, close the valve in the service port of the track
- Put the tractor into float mode
- Go back to the track, hold the gauge in one hand, and slowly crack open the valve with the other hand until the pressure comes back down to 110 bar (1600 psi)
- Close everything off, disconnect hose and gauge, reinstall service port cover plate

Feature: Mounts close to machine, similar length as OEM tracks

Benefits: Much easier on final drives of combine

Operating

Feature: Oscillating bogie system

Benefits: Bogie axles “flex” with the lay of the land, creating a comfortable ride with maximum ground contact