

## SEEDING BOOM FOR P-BOX-STI

- » Flexible device for front or rear mounting
- » Many different applications:
  - Fertilising
  - Seeding of catch crops
  - Grass reseeding
  - Spreading undersown crops
- » Can be combined with many (rear) implements:
  - Cultivator, row-crop cultivator, tined weeder, etc.

### Technical data:

- » Mechanically or hydraulically foldable
- » 6 m / 19.70 ft. working width
- » 8 outlets at a distance of 75 cm / 29.50" (easily adjustable)
- » Practical castors - for easy manoeuvring around the yard
- » Various tank sizes (265l/300l/500l) and tank types (plastic/metal) available
- » Various fan variants (electric/hydraulic) available
- » Weight including P-BOX-STI, steps and hoses: 340 kg / 750 lbs  
(with steps, without P-BOX-STI and hoses: 225 kg / 496 lbs)



### WITH P-BOX-STI AND ALL ITS FAMILIAR ADVANTAGES:

- » Large colour 5-inch display
- » Clear and colourful menu navigation
- » Many individual setting options
- » Intuitive, simple and automatic calibration test
- » 2 seeding rollers (1 with coarse and 1 with fine toothing)
- » Seeding roller can be changed without tools
- » Each seeding roller with separate section per hose
- » Calibration plate and calibration pan
- » Discharge opening and monitoring window

### EXTENSIVE SENSOR SELECTION:

- » Sensor values from the tractor can be transferred via the 7-pin signal socket (speed & lifting signal)
- » The GPS sensor on the lid cap provides precise speed information
- » The upper link sensor automatically switches off the seeding roller when the implement is raised (not required with 7-pin cable)
- » Sensor for tank level control - indicates before the seed is used of
- » Calibration button on the device - for carrying out the calibration test directly on the device

